



SPRO-100W / 50W / 30W / 20W / 10W Floodlight Series



Features & Benefits

- ✓ 膏導熱的結構(銅基板)
- ✓ 光源 COB 多晶封裝
- ✓ 節能省電、環保健康
- ✓ 品質保證 台灣製造

Specifications



10W~30W 可選加感應器

感應器

感應器

感應器

型號 (Model)	SPRO-100W		SPRO-50W		SPRO-30W		SPRO-20W		SPRO-10W		
瓦數 (Wattage)	100W		50W		30W		20W		10W		
電壓 (Input Voltage)	AC 100~277V, 50/60Hz		AC 100~277V, 50/60Hz		AC 100~277V, 50/60Hz		AC 100~277V, 50/60Hz		AC 100~277V, 50/60Hz		
色溫 (CCT)	5700K	3000K	5700K	3000K	5700K	3000K	5700K	3000K	5700K	3000K	
角度 (Field Angle)	150°		150°		150°		150°		120°		
光通量 (Flux)	8000 lm	6600 lm	4500 lm	3500 lm	2600 lm	2200 lm	1800 lm	1500 lm	620 lm	520 lm	
照度 (Luminous Intensity)	Lux@1M	2200 Lux@1M	1800 Lux@1M	1300 Lux@1M	975 Lux@1M	750 Lux@1M	610 Lux@1M	520 Lux@1M	416 Lux@1M	173 Lux@1M	138 Lux@1M
	Lux@2M	600 Lux@2M	500 Lux@2M	360 Lux@2M	270 Lux@2M	208 Lux@2M	170 Lux@2M	155 Lux@2M	115 Lux@2M	--	--
	Lux@3M	300 Lux@3M	200 Lux@3M	178 Lux@3M	140 Lux@3M	104 Lux@3M	85 Lux@3M	--	--	--	--
	Lux@4M	150 Lux@4M	120 Lux@4M	95 Lux@4M	70 Lux@4M	--	--	--	--	--	--
演色性 (CRI)	70	77	70	77	70	77	70	77	70	77	
尺寸 (Dimension)	 L: 380mm W: 285mm H: 75mm		 L: 235mm W: 280mm H: 110mm		 L: 183mm W: 220mm H: 105mm		 L: 140mm W: 180mm H: 85mm		 L: 85mm W: 115mm H: 80mm		
重量 (Weight)	3608g ± 10%		2100g ± 10%		1440g ± 10%		931g ± 10%		390g ± 10%		
壽命 (Lifetime)	30,000 hours		30,000 hours		30,000 hours		30,000 hours		30,000 hours		
保固 (Warranty)	1-Year		1-Year		1-Year		1-Year		1-Year		