



Shenzhen Zoyo Electronics Co.,Ltd.

Add. ;E Bldg.,Xinhui Industrial Park,
No.3 Tangtou Industrial Zone,
Shiyan Town,Baoan Dist.
Shenzhen,China.518108
www.zoyoled.com

Down Light Series:

1、Ruby Series

4in' size of dia.126mm*60mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DR406I-W	AC 110/ AC 220	6	6000	83	>80	105
DR406I-S	AC 110/ AC 220	6	4500	82	>80	105
DR406I-WW	AC 110/ AC 220	6	3000	80	>80	105

6in' size of dia.186mm*63mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DR612I-W	AC 110/ AC 220	12	6000	86	>80	105
DR612I-S	AC 110/ AC 220	12	4500	85	>80	105
DR612I-WW	AC 110/ AC 220	12	3000	82	>80	105

6in' size of dia.240mm*75mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DR824I-W	AC 110/ AC 220	24	6000	88	>80	105
DR824I-S	AC 110/ AC 220	24	4500	86	>80	105
DR824I-WW	AC 110/ AC 220	24	3000	83	>80	105

Features:

1. Surface design with the Anti glare, appearance and structure are patented.

- 2.Integrated design, lighter and thinner in structure.
- 3.Shell material with high purity aluminum, better heat dissipation.
- 4.High quality and transmittance PC lens insuring high Light Efficiency.
- 5.Wide Input voltage, no strobe and start response without delay.
- 6.Isolated power and cover designing resulting good security and reliability.
- 7.More than 5 years life span if working 10 hours per day.

Application:

Home furnishing, Shopping mall, Boutique Traders Hotel ,Restaurant, office, brand chain stores and other indoor lighting area.



2、Saphire Series

4in' size of dia. 140mm*62mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DS406I-W	AC 110/ AC 220	6	6000	83	>80	110
DS406I-S	AC 110/ AC 220	6	4500	82	>80	110
DS406I-WW	AC 110/ AC 220	6	3000	80	>80	110

6in' size of dia. 192mm*67mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DS612I-W	AC 110/ AC 220	12	6000	86	>80	110
DS612I-S	AC 110/ AC 220	12	4500	85	>80	110
DS612I-WW	AC 110/ AC 220	12	3000	82	>80	110

8in' size of dia. 240mm*72mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DS824I-W	AC 110/ AC 220	24	6000	88	>80	110
DS824I-S	AC 110/ AC 220	24	4500	86	>80	110
DS824I-WW	AC 110/ AC 220	24	3000	83	>80	110

Features:

1. Surface design super light emitting, appearance and structure are patented.
- 2.Integrated design, lighter and thinner in structure.
- 3.Shell material with high purity aluminum, better heat dissipation.
- 4.High quality and transmittance PC lens insuring high Light Efficiency.
- 5.Wide Input voltage, no strobe and start response without delay.
- 6.Isolated power and cover designing resulting good security and reliability.
7. More than 5 years life span if working 10 hours per day.

Application:

Home furnishing, Shopping mall, Boutique Traders Hotel ,Restaurant, office, brand chain stores and other indoor lighting area.



3、Zoisite Series

3in size of dia. 110mm*82mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DZ310C-W	AC 110/ AC 220	10	6000	82	>80	60/40
DZ310C -S	AC 110/ AC 220	10	4500	80	>80	60/40
DZ310C -WW	AC 110/ AC 220	10	3000	78	>80	60/40

4in size of dia. 140mm*96mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DZ415C -W	AC 110/ AC 220	15	6000	82	>80	60/40
DZ415C -S	AC 110/ AC 220	15	4500	80	>80	60/40
DZ415C -WW	AC 110/ AC 220	15	3000	78	>80	60/40

5in size of dia. 160mm*96mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DZ520C -W	AC 110/ AC 220	20	6000	85	>80	60/40

DZ520C -S	AC 110/ AC 220	20	4500	82	>80	60/40
DZ520C -WW	AC 110/ AC 220	20	3000	80	>80	60/40

6 in size of dia. 195mm*93mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DZ625C -W	AC 110/ AC 220	25	6000	86	>80	60/40
DZ625C -S	AC 110/ AC 220	25	4500	83	>80	60/40
DZ625C -WW	AC 110/ AC 220	25	3000	80	>80	60/40

Features:

1. Unique appearance design ,appearance and structure are patented.
- 2.Shell material with high purity aluminum, better heat dissipation.
- 3.Adopted COB LED source, compatible with CREE,CITIZEN,BRIDGELUX LED source.
- 4.Wide Input voltage, no strobe and start response without delay.
- 5.Isolated power and cover designing resulting good security and reliability.
- 6.Light beam angles optional in 40 °,60 °.
- 7.More than 5 years life span if working 10 hours per day.

Application:

Home furnishing, Shopping mall, Boutique Traders Hotel ,Restaurant, office, brand chain stores and other indoor lighting area.



4、Amerald Series

4in size of dia. 140mm*140mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DA415C -W	AC 110/ AC 220	15	6000	82	>80	13/27/40
DA415C -S	AC 110/ AC 220	15	4500	80	>80	13/27/40
DA415C -WW	AC 110/ AC 220	15	3000	78	>80	13/27/40

6 in size of dia. 170mm*150mm and specifications as bellow:

Order No.	Input Voltage(V)	Power(W)	Color Temperature (K)	Light Efficiency (Lm/W)	Ra	beam Angle(°)
DA625C -W	AC 110/ AC 220	25	6000	86	>80	13/27/40
DA625C -S	AC 110/ AC 220	25	4500	83	>80	13/27/40
DA625C -WW	AC 110/ AC 220	25	3000	80	>80	13/27/40



Features:

1. Unique appearance design ,appearance and structure are patented.
- 8.Shell material with high purity aluminum, structure of thermal convection with good thermal transmission.

9. Adopted COB LED source, compatible with CREE, CITIZEN, BRIDGELUX LED source.

10. Wide Input voltage, no strobe and start response without delay.

11. Isolated power and cover designing resulting good security and reliability.

12. Light beam angles optional in 13°, 27°, 40°.

13. Front ring with four colors R/G/Y/Black optional.

14. More than 5 years life span if working 10 hours per day.

Application:

Home furnishing, Shopping mall, Boutique Traders Hotel, Restaurant, office, brand chain stores and other indoor lighting area.